

Insulated Food Servers (Electric) — Camtherm® Electric Food Holding Cabinets



Go From Hot to Cold in One Versatile Appliance!

- Use for bulk food holding in the kitchen or to transport large amounts of food off-site.
- Go from hot to cold with the simple flip of a switch!
- Tough polyethylene exterior will not dent, rust or chip; stays cool to the touch during operation, unlike metal cabinets.
- Thick polyurethane foam insulation maintains safe food holding temperatures for 4 hours or more, even unplugged.
- Available in two sizes and hot only or hot/cold models.

Energy-efficient thermoelectric heating and cooling with:

No Compressor, heating coil or humidifier.

Low voltage, amps, wattage.



48%

More Energy Efficient

Than a Leading Metal Cabinet

Insulated Food Servers (Electric)



Camtherm® Electric Food Holding Cabinets



ADJUSTABLE CHROME-PLATED STEEL SLIDE RAILS
Hold full-size food pans or sheet pans.

POLYETHYLENE EXTERIOR
Stays cool to the touch during operation.

ERGONOMIC MOLDED-IN HANDLES
For easy maneuvering even when fully loaded.

ALUMINUM LOUVERS
Gently circulate hot or cold air evenly.

WIDE NYLON DOOR LATCHES/MAGNETIC DOOR GASKETS
Lock doors securely and create a tight seal to retain safe hot or cold food temperatures.

MOLDED-IN BUMPERS
Protect walls and furniture.

CONTROL PANEL (in back) On/Off switch
Temperature control dial for hot only models
[Hot pre-set between 150° to 165°F (65° to 74°C)].

Hot/Cold switch for Hot/Cold Models only
[Cold pre-set to 37°F (2,8°C)].

TRANSITION TIME
Cold to Hot: 3 hrs.
Hot to Cold: 1.5 to 2.5 hrs.

KNUCKLE DOOR HINGES
Withstand rigorous door openings, allows door to be lifted up and off for easy cleaning.

DOOR SWINGS OPEN 270°
for easy loading.

MARINE RAILING
Holds 2 full-sized food pans, 1 full-sized sheet pan or cutting board (CB1220).



SOLAR DIGITAL THERMOMETER
Monitor internal temperature at a glance.

SELF-VENTING CAP
Releases steam and equalizes pressure, maintaining food quality.

MENU CLIP
For easy product/event identification.

Camtherm® Electrical Specifications



ELECTRICAL SPECIFICATIONS	LOW PROFILE HOT ONLY	LOW PROFILE HOT/COLD	TALL PROFILE HOT ONLY	TALL PROFILE HOT/COLD
VOLTS	110V	110V	110V	110V
PLUG TYPE	Nema 5-15P	Nema 5-15P	Nema 5-15P	Nema 5-15P
MAXIMUM AMP DRAW	9.1 amps	10.7 amps	14 amps	14.3 amps
AMPS RUN ON	9 amps	10.1 amps	13.8 amps	13.6 amps
WATTS	1035	1162	1587	1570
HERTZ	50/60	50/60	50/60	50/60
POWER INPUT OF HEATING UNIT	110-120 VAC	110-120 VAC	110-120 VAC	110-120 VAC

Assembly is covered by U.S. Patent D 442,756 S & D 6,344,630.

Insulated Food Servers (Electric)

Camtherm® Capacity Specifications

HOLDING CAPACITY	LOW PROFILE	HIGH PROFILE
Sheet Pans		
18" x 26" (45,7 x 66 cm)	11*	22**
Full-Size Food Pans		
2½" (6,5 cm) Deep	12	24
4" (10 cm) Deep	8	16
6" (15 cm) Deep	6	12
8" (20 cm) Deep	4	8

*Requires five additional rail sets

**Requires five additional rail sets.


Security Package

Models are specifically modified with tamper-resistant hardware for operations where safety is a top priority.


- Security screws attach rail assembly to unit.
- Locking, stainless steel door latch—factory assembled.
- One-piece, welded rail and upright assembly available upon request.



Product Specifications CAD Drawings, Cut Sheets and User Manual Available at www.cambro.com.

	CODE	THERMOMETER	CASTERS	UNIT WEIGHT LBS	LIST PRICE EA.	
	LOW PROFILE					
	EXTERIOR dimensions: W 30½" x D 42" x H 42¾"					
	<i>Hot Only</i>					
		CMBH1826LF	Fahrenheit	2 front 6" swivel w/brake, 2 rear 10" rigid	164	\$ 6,020.00
		CMBH1826LC	Celsius	2 front 6" swivel w/brake, 2 rear 10" rigid	164	6,020.00
	<i>Hot/Cold</i>					
		CMBHC1826LF	Fahrenheit	2 front 6" swivel w/brake, 2 rear 10" rigid	222	14,195.00
		CMBHC1826LC	Celsius	2 front 6" swivel w/brake, 2 rear 10" rigid	222	14,195.00
	LOW PROFILE WITH SECURITY PACKAGE					
		<i>Hot Only</i>				
	CMBH1826LSP	Fahrenheit	2 front 6" swivel w/brake, 2 rear 10" rigid	167.4	6,305.00	
	<i>Hot/Cold</i>					
	CMBHC1826LSP	Fahrenheit	2 front 6" swivel w/brake, 2 rear 10" rigid	225.4	14,520.00	



	TALL PROFILE					
	EXTERIOR dimensions: W 30½" x D 39" x H 64¾"					
	<i>Hot Only</i>					
		CMBH1826TSF	Fahrenheit	2 front 6" swivel w/brake, 2 rear 6" rigid	250	9,405.00
		CMBH1826TBF	Fahrenheit	2 front 6" swivel w/brake, 2 rear 10" rigid	254	9,405.00
		CMBH1826TSC	Celsius	2 front 6" swivel w/brake, 2 rear 6" rigid	250	9,405.00
		CMBH1826TBC	Celsius	2 front 6" swivel w/brake, 2 rear 10" rigid	254	9,405.00
	<i>Hot/Cold</i>					
		CMBHC1826TSF	Fahrenheit	2 front 6" swivel w/brake, 2 rear 6" rigid	325.5	19,940.00
		CMBHC1826TBF	Fahrenheit	2 front 6" swivel w/brake, 2 rear 10" rigid	330	19,940.00
		CMBHC1826TSC	Celsius	2 front 6" swivel w/brake, 2 rear 6" rigid	325.5	19,940.00
		CMBHC1826TBC	Celsius	2 front 6" swivel w/brake, 2 rear 10" rigid	330	19,940.00
	TALL PROFILE WITH SECURITY PACKAGE					
		<i>Hot Only</i>				
		CMBH1826TSP	Fahrenheit	2 front 6" swivel w/brake, 2 rear 10" rigid	260.77	9,925.00
	<i>Hot/Cold</i>					
	CMBHC1826TSP	Fahrenheit	2 front 6" swivel w/brake, 2 rear 10" rigid	337	20,465.00	
Cabinet Colors: Granite Gray (191), Granite Green (192), Granite Sand (194).						



CONFORMS TO UL STD 197 & 471; ANSI/NSF STD 4

ACCESSORIES	CODE	DESCRIPTION	DIMENSIONS L x W x H	CASE PACK	LIST PRICE EA.
	CMBR	Set of Slide Rails	20" x 4 13/16"	1 set of 2 Rails	\$ 55.00
	CB1220	Cutting Board	21" x 13 7/8" x 1/2"	1 each	42.00

Cutting Board Color: White (148). Venting plug is covered by US Patent D 553,717 S.