



Stainless design.
Stellar performance.
Superior value.

AR49
Refrigerator

AF49
Freezer

Two Door Reach-in Refrigerators and Freezers

- *Tested to NSF Standard 7 requirements for open food storage.*
- *Arctic Air products must pass numerous quality control inspections throughout the manufacturing process. All products are operated and monitored for a minimum of thirteen hours prior to packaging and shipping.*
- *All Arctic Air products come with full one year parts and labor warranties and a five year compressor warranty.*



Two Door Reach-in Refrigerators and Freezers

Stainless design. Stellar performance. Superior value.


- 
- Exterior cabinet construction consists of full stainless steel front and sides.
 - Electronic thermostat with external digital LED display for accurate control and easy reading.
 - Interior cabinet is bright white aluminum liner with full stainless steel floor with coved corners.
 - Six adjustable, heavy-duty epoxy coated wire shelves.
 - Self contained capillary tube system using environmentally friendly CFC free refrigerant (R404A in freezers and R134A in refrigerators).
 - Condensate heating element built into condensate pan for efficient evaporation of excess water.
 - Bottom mounted compressor for more efficient operation in coolest area of the kitchen.
 - Front accessible, bottom mounted condensing unit is mounted on slide out rack for easy maintenance.
 - Self closing doors that remain open at 90 degrees.
 - Magnetic door gaskets are removable and replaceable without tools.
 - Freezer doors have integral factory installed heating element to eliminate condensation.
 - Lockable doors with foamed-in-place recessed handles.
 - Larger fan motors and blades for more efficient air flow ensuring faster recovery times.
 - Easy to mount casters (two lockable) are standard with all units.
 - Tested to NSF Standard 7 requirements for open food storage.
 - All Arctic Air products come with full one year parts and labor warranties and a five year compressor warranty.

Model Number	External Dimensions			Doors	Shelves	Cubic Feet	Temperature Range	Cord Length	HP	Amps	NEMA Plug	Crated Weight (lbs.)
	Width	Depth*	Height**									
AR49	54"	32.75"	82.75"	2	6	49	33°F to 41°F	9	1/2	7	5-15P	455
AF49	54"	32.75"	82.75"	2	6	49	-10°F to +10°F	9	1	12	5-15P	485

*Depth with door open 90° — AR49/AF49 = 57.75" **Height includes 6" for casters

Optional Shelf Kit (#65056K)

Each kit contains one shelf and four mounting clips.



COMMERCIAL FREEZERS & REFRIGERATORS



ANSI/NSF 7